

B\$D-2W – Direct File Access Simple Write Next Routine

The B\$D-2W routine is one of a family of sub-routines that are reserved for use by the G-3000 Middleware DLMs. B\$D-2W(RITE) writes a record to the BDAM file.

1. Invocation

To write a record to the BDAM file code:

```
CALL B$D-2W USING record rec_len
```

where *record* is the PIC X(n) record area and *rec_len* is a PIC 9(4) COMP variable, or literal, containing the length of the record to write.

2. STOP Codes and Exception Conditions

No STOP codes are generated by B\$D-2W.

The following EXIT codes may be returned by B\$D-2W:

EXIT code	\$\$COND	Description
1	1	It was not possible to write the record (the file is full)

3. Programming Notes

B\$D-2W(RITE) has been derived from a G-3000 Middleware DLM. Consequently, some of the functionality (e.g. the EXIT codes) may be non-standard.

The BO\$G3M DLM, rather than the calling program, contains the File Definition (FD) used for the various Direct Access File operations. The *rec_len* parameter is moved to the Record Length field (FDBLO) in the internal FD. The current FDFAD field in the internal FD is expected to contain the File Address. If the write operation succeeds the File Address field (FDFAD) is increased by Record Length (FDBLO).

4. Examples

[EXAMPLE REQUIRED]

5. Copy-Books

None.

6. See Also

B\$D-2R	Direct File Access Simple Read Next Routine (B\$D-2RNXT)
B\$D-CH	Direct File Access Check and Close Routine (B\$D-CHK)
B\$D-CL	Direct File Access Close Routine (B\$D-CLOSE)
B\$D-DE	Direct File Access Delete Routine (B\$D-DELETE)
B\$D-IN	Direct File Access Return File Information Routine (B\$D-INFO)
B\$D-OL	Direct File Access Open Old Routine (B\$D-OLD)
B\$D-OP	Direct File Access Open New Routine (B\$D-OPEN)
B\$D-PO	Direct File Access Set Current File Position Routine (B\$D-POSITION)
B\$D-UN	Direct File Access Set Unit Routine (B\$D-UNIT)
B\$D-WR	Direct File Access Write Speedbase Channel (B\$D-WRITE)

B\$D-2W – Direct File Access Simple Write Next Routine

B\$E-CL	Direct File Access Extra Close Routine (B\$E-CLOSE)
B\$E-GE	Direct File Access Get Record Length Routine (B\$E-GET-RLEN)
B\$E-RN	Direct File Access Simple Read Block Routine (B\$E-RNXT)
B\$E-SE	Direct File Access Set Record Length Routine (B\$E-SET-RLEN)
B\$E-ZE	Direct File Access Set File Address to Zero Routine (B\$E-ZERO)
R\$B-SA	Direct File Access Save Address of Current Record (R\$B-SAVE)
R\$B-WR	Direct File Access Rewrite from Saved File Address (R\$B-WRITE)
R\$B2WR	Direct File Access Rewrite from Saved File Address (R\$B2WRITE)
R\$PFSC	Direct File Access Check For Free Space (R\$PFSCCHK)