

GXBCO\$ - Change Window Background Colour

The GXBCO\$ routine can be used to change the background colour of a Speedbase window displayed by GX.

1. Invocation

To change the window background colour code:

```
CALL GXBCO$ USING bc
```

where *bc* is a control block of the following format:

```
01      BC
02      BCVERS      PIC 9(4) COMP      * Version number, must be 1
02      BCFLAG      PIC 9(2) COMP      * 0 = Reset background colour to default
                                           * 1 = Set explicit background colour
02      BCRED        PIC 9(4) COMP      * Red colour component
02      BCGREEN      PIC 9(4) COMP      * Green colour component
02      BCBLUE       PIC 9(4) COMP      * Blue colour component
```

2. STOP Codes and Exception Conditions

The following STOP codes may be generated by GXBCO\$:

STOP code	Description
23967	GXBCO\$ has been called by an application that is not running on GX.
23968	Invalid block version number in BCVERS

No EXIT codes are returned by GXBCO\$.

3. Programming Notes

This routine is only available with GSM SP-29, or later.

GXBCO\$ is only available when running on GX. Any attempt to use GXBCO\$ on a non-GX terminal will result in a STOP code.

GXBCO\$ only affects the current in-focus window.

4. Examples

[EXAMPLE REQUIRED]

5. Copy-Books

None.

6. See Also

None.

GXBCO\$ - Change Window Background Colour