

GXCPH\$ - Set GX Contract Protection Message Help Text

The GXCPH\$ routine is available to set the GX Contract Protection Message Help Text, as displayed by the Help/About box.

THIS ROUTINE IS RESERVED FOR INTERNAL USE ONLY.

1. Invocation

To set the GX Contract Protection Message Help Text code:

```
CALL GXCPH$ USING text
```

where *text* is the text-string **WHICH MUST BE TERMINATED WITH A BINARY ZERO** (i.e. a byte of LOW-VALUES).

2. STOP Codes and Exception Conditions

The following STOP codes may be generated by GXCPH\$:

STOP code	Description
23926	GXCPH\$ has been called by an application that is not running on GX.
23927	The total length of the GX command block has exceeded an internal limit.
23928	An attempt was made to call GXCPH\$ on an incompatible version of GX. The version of GX must be V2.7, or later.
23929	An unexpected error has been reported by GX

The following EXIT codes may be returned by GXCPH\$.

EXIT code	\$\$COND	Description
23922	22	Unable to allocate memory for temporary work buffer

3. Programming Notes

GXCPH\$ is only available when running on GX. Any attempt to use GXCPH\$ on a non-GX terminal will result in a STOP code.

IMPORTANT NOTE: GXCPH\$ IS RESERVED FOR USE BY INTERNAL SOFTWARE AND IS DOCUMENTED FOR COMPLETENESS ONLY. THE RESULTS OF ATTEMPTING TO USE THIS ROUTINE IN AN APPLICATION ARE UNPREDICTABLE.

4. Examples

[EXAMPLES REQUIRED]

5. Copy-Books

None.

6. See Also

None.