

## GXCPM\$ - Set GX Contract Protection Message

The GXCPM\$ is available to display the GX Contract Protection Message. This routine is only used by \$STARX.

**THIS ROUTINE IS RESERVED FOR INTERNAL USE ONLY.**

### 1. Invocation

To set the GX Contract Protection Message code:

```
CALL GXCPM$ USING timeout text
```

where *timeout* is a PIC 9(4) COMP field, or literal, and *text* is the text-string **WHICH MUST BE TERMINATED WITH A BINARY ZERO** (i.e. a byte of LOW-VALUES).

### 2. STOP Codes and Exception Conditions

The following STOP codes may be generated by GXCPM\$:

STOP code	Description
?????	GXCPM\$ has been called by an application that is not running on GX.
?????	String too large for internal buffer
?????	An attempt was made to call GXCPM\$ on an incompatible version of GX. The version of GX must be V2.7, or later.
?????	An unexpected error has been reported by GX

The following EXIT codes may be returned by GXCPM\$.

EXIT code	\$\$COND	Description
?????	??	Unable to allocate memory for temporary work buffer

### 3. Programming Notes

GXCPM\$ is only available when running on GX. Any attempt to use GXCPM\$ on a non-GX terminal will result in a STOP code.

**IMPORTANT NOTE: GXCPM\$ IS RESERVED FOR USE BY INTERNAL SOFTWARE AND IS DOCUMENTED FOR COMPLETENESS ONLY. THE RESULTS OF ATTEMPTING TO USE THIS ROUTINE IN AN APPLICATION ARE UNPREDICTABLE.**

#### **4. Examples**

[EXAMPLES REQUIRED]

#### **5. Copy-Books**

None.

#### **6. See Also**

None.