

# GXFIC\$ - Close Find Handle on GX

The GXFIC\$ routine is used to close the file handle created by a successful call to GXFIF\$ (and used by subsequent calls to GXFIN\$).

## 1. Invocation

To close the Find Handle on GX code:

```
CALL GXFIC$ USING fi
```

where *fi* is a control block of the following format:

```

01  FI
02  FIWILD      PIC PTR          * NOT USED
02  FILLER      PIC 9(9) COMP    * RESERVED FOR USE BY GXFIC$
02  FIATTR      PIC 9(9) COMP    * NOT USED
02  FINAME      PIC PTR          * NOT USED
    
```

The same *fi* block that was used for a previous successful call to GXFIF\$ **must** be used for the final call to GXFIC\$.

## 2. STOP Codes and Exception Conditions

The following STOP codes are returned by GXFIC\$.

STOP code	Description
14450	GXFIC\$ has been called by an application that is not running on GX.

The following EXIT codes may be returned by GXFIC\$:

EXIT code	\$\$COND	Description
14410	10	Internal error type-1 in GXFIC\$.
14411	11	Internal error type-2 in GXFIC\$.
14412	12	A Windows error has been detected by GX. The Windows result code is available in the \$\$CRES System Variable.

### 3. Programming Notes

The GXFIC\$ routine must be used in conjunction with the GXFIF\$ and GXFIN\$ routines.

GXFIC\$ can only be used after a successful call to GXFIF\$. The combination of GXFIF\$ & GXFIN\$ **MUST** be followed by a final call to GXFIC\$.

### 4. Examples

[EXAMPLES REQUIRED].

### 5. Copy-Books

None.

### 6. See Also

GXFIF\$ Find First File on GX

GXFIN\$ Find Next File on GX

GXFIC\$ - Close File Handle on GX