

GXGLR\$ - Get Location Reference from GXHOSTS.INI

The GXGLR\$ routine can be used to obtain the Location Reference setting from the GXHOSTS.INI file.

1. Invocation

To obtain the Location Reference setting code:

```
CALL GXGLR$ USING name
```

where *name* is a PIC X(100) field into which the Location Reference setting is returned.

2. STOP Codes and Exception Conditions

The following STOP codes may be generated by GXGLR\$:

STOP code	Description
14203	GXGLR\$ has been called by an application that is not running on GX

No exceptions are returned by GXGLR\$.

3. Programming Notes

GXGLR\$ is only available when running on GX. Any attempt to use GXGLR\$ on a non-GX terminal will result in a STOP code.

The Location Reference setting is defined in the [hosts] section of the GXHOSTS.INI file. For example:

```
[hosts]
HostID1=localhost,Local host
LocationReference1=LocationRef1
```

The Location Reference setting is **NOT** terminated with a byte of binary-zero. If the Location Reference setting is less than 100 characters, the remainder of the PIC X(100) field is SPACE filled.

4. Examples

[EXAMPLES REQUIRED]

5. Copy-Books

None.

6. See Also

GXGUN\$ Get Windows user name
 GXGCN\$ Get Windows computer name
 GXGCR\$ Get Computer Reference from GXHOSTS.INI

