GXGOS$ - Return Windows O/S Information from the GX PC

The GXGOS$ routine is available to return a Windows O/S string from the PC running GX.

1.   Invocation

The GXGOS$ routine is called as follows:

```
CALL GXGOS$ USING buffer
```

where *buffer* is a PIC X(1024) buffer into which the Windows O/S information is returned. The returned string is zero-terminated.

2.   STOP Codes and Exception Conditions

The following STOP codes may be generated by GXGOS$:

STOP code	Description
14203	GXGOS$ has been called by an application that is not running on GX.

The following exception conditions may be returned by GXGOS$:

EXIT code	$$COND	Description
14212	12	An exception was returned by GX.

3.   Programming Notes

GXGOS$ is only available when running on GX. Any attempt to use GXGOS$ on a non-GX terminal will result in a STOP code. GXGOS$ is only available with GX V4.7r, or later. Any attempt to use GXGOS$ on an earlier version of GX will result in an exception. Furthermore, GXGOS$ is only available with GSM SP-36, or later.

4.   Examples

[EXAMPLE REQUIRED]

5.   Copy-Books

None.

6.   See Also

GXGTZ$ Get Time Zone information from the GX PC
GXMAC$ Get MAC Address information from the GX PC
GXGIP$ Get IP Address information from the GX PC
GXGSS$ Get Screen Size information from the GX PC
GXGWS$ Get Window Size information from the GX PC

GXGKN$ Get Computer Name information from the GX PC
GXPCE$ Apply Percent Encoding to a String

GXGKN$ Get Computer Name information from the GX PC
GXPCE$ Apply Percent Encoding to a String