

GXOPI\$ - Set GX Operator-ID Text

The GXOPI\$ routine is available to set the GX Operator-ID text as displayed in the GX Status Bar.

THIS ROUTINE IS RESERVED FOR INTERNAL USE ONLY.

1. Invocation

To set the GX Operator-ID text code:

```
CALL GXOPI$
```

2. STOP Codes and Exception Conditions

The following STOP codes may be generated by GXOPI\$:

STOP code	Description
23926	GXOPI\$ has been called by an application that is not running on GX.
23927	This STOP code should never occur
23928	An attempt was made to call GXOPI\$ on an incompatible version of GX. The version of GX must be V2.7, or later.
23929	An unexpected error has been reported by GX

The following EXIT codes may be returned by GXOPI\$.

EXIT code	\$\$COND	Description
23922	22	Unable to allocate memory for temporary work buffer

3. Programming Notes

GXOPI\$ is only available when running on GX. Any attempt to use GXOPI\$ on a non-GX terminal will result in a STOP code.

GXOPI\$ currently uses the PIC X(4) Operator-id field from the \$\$OPID System Variable.

IMPORTANT NOTE: GXOPI\$ IS RESERVED FOR USE BY INTERNAL SOFTWARE AND IS DOCUMENTED FOR COMPLETENESS ONLY. THE RESULTS OF ATTEMPTING TO USE THIS ROUTINE IN AN APPLICATION ARE UNPREDICTABLE.

4. Examples

[EXAMPLES REQUIRED]

5. Copy-Books

None.

6. See Also

None.