

WWW\$ - Invoke an Internet Browser with a URL

The WWW\$ routine is available to invoke an Internet Browser with a URL on the PC running the GX (or GSMWIN32.EXE) thin-client.

1. Invocation

To invoke an Internet Browser with a URL code:

```
CALL WWW$ USING st
```

where *st* is a control block of the following format:

```
01      ST
02      STLEN          PIC 9(4) COMP          * Length of URL string
02      STURL          PIC PTR                * Pointer to URL string
```

2. STOP Codes and Exception Conditions

The following STOP codes may be generated by WWW\$:

STOP code	Description
13601	WWW\$ has been called on a PC that is not running GX (or GSMWIN32.EXE).

No EXIT codes are returned by WWW\$.

3. Programming Notes

For GX, the full pathname of the required Web Browser must be specified by the WebBrowser setting in the [miscellaneous] section of the GXIO.INI file. For example:

```
WebBrowser=C:\Program Files (x86)\Mozilla Firefox\firefox.exe
```

Note that length of the URL string text must be supplied in STLEN and must be nonzero i.e. a zero-terminated text-string cannot be supplied. This is, perhaps, a shortcoming of WWW\$.

4. Examples

[EXAMPLE REQUIRED]

5. Copy-Books

None.

6. See Also

WWW2\$ Invoke an Internet Browser with a local file